## TIMETRAX™ SYNC CLOCK WASH DOWN ENCLOSURE Installation Instructions 42689, 42690 SIMPLE SMART™

## **OVERVIEW**


Thank you for choosing a TimeTrax<sup>™</sup> Sync Clock Wash-Down Enclosure (42689/42690). This lightweight, durable plexiglass enclosure kit is used to protect analog or digital wall clocks from dust, dirt, grime, debris & splash in harsh indoor environments. The enclosure features a gasket for sealed installation and is NEMA 4 compliant. Enclosure is constructed with pre-drilled holes for easy mounting.

ModelUse With42689Digital Clocks4269013in Analog Clock

The wash down enclosure is also suitable for lights, signs and other devices.

For more information, visit pyramidtimesystems.com or call our technical support team at 888.479.7264 during regular business hours: 8am-5pm EST, M-F.

### KIT CONTENTS



42689 42690
Digital Wash Down Enclosure Analog Wash Down Enclosure

## ,,,,,,

Mounting Screws (6)


## **INSTALLATION**

- ① Center wash down enclosure over clock. Adjust as required to level the Enclosure. A torpedo level is recommended. Mark the location of the six mounting holes.
- Remove enclosure & drill holes at marked locations using a 1/6in drill bit. If wall anchors (included) are used, drill hole size as per wall anchor instructions.
- 3 Replace the enclosure over the clock & attach to wall with six #10 screws (included). Be sure to tighten screws enough to create a seal between gasket & wall surface.

#### NOTE:

Tighten the screws to slightly compress the gasket. Over tightening may cause the gasket not to seal in areas between screws. If enclosure is to be used with a clock installed on a masonry wall or irregular surface, sealant is required. Place a bead of clear silicone caulk on gasket. Quantity or thickness of the caulk bead is determined by degree of surface irregularity.











# TIMETRAX™ SYNC CLOCK WASH DOWN ENCLOSURE Installation Instructions 42689, 42690

SI	NΛ	PI	F	0	M	Δ	RT	- TM
~ 1	1 W 1	1	- Brownie	U 1	21 V.I	4.		

SPECIFICATIONS						
Construction Ple		exiglass				
Finish CI		Clear				
Mounting Wa		Vall				
Warranty 3-		Year manufacturer's limited warranty				
Guarantee 30		-Day money back guarantee				
		nalog or Digital Wash Down Enclosure, 6 mounting crews, 6 wall anchors				
SIZE		42689	42690			
Dimensions		18.25inW x 9.25inH x 2inD (46.35cm x 23.49cm x 5.08cm)	16.5in Diameter x 3.25in D (41.91cm x 8.255cm)			
Weight		1.05lbs (.476kg)	1.35lbs (.612kg)			
Shipping Weight		1.55lbs (.703kg)	2.15lbs (.975kg)			

ADDITIONAL CLOCK ACCESSORIES						
PART#	DESCRIPTION					
42320	Dual Analog Clock Wall Bracket (13in)					
42321	Dual Digital Clock Wall Bracket (3x4/2.5x6/4x4)					
42422	Dual Digital Clock Wall Bracket (4x6)					
42443	Dual Clock Ceiling Bracket					
42314	Dual 13in Analog Clock Chrome Wire Guard					
42315	Dual 17in Analog Clock Chrome Wire Guard					
42316	4in x 6 digit Digital Clock Chrome Wire Guard					
42400	4in x 4 digit Digital Clock Chrome Wire Guard					
42401	2.5in x 6 digit Digital Clock Chrome Wire Guard					
42690	13in Analog Clock Wash Down Enclosure					
42689	Digital Clock Wash Down Enclosure					
42247	Digital Security Mount Replacement					
42281	Wall Clock Security Mount Replacement Key					

